


GENERAL NOTES:

- 1. THE FOUNDATION IN THE DRAWING TO BE USED AS A MININUM GUIDELINE. CHECK WITH LOCAL ENGINEERS
- 2. THE CONCRETE SHALL BE GRADE C25 (CHARACTERISTIC STRENGTH OF 3500 PSI AT 28 DAYS) MINIMUM.
- 3. THE FOUNDATION SHALL BE PLACED ON FIRM, UNDISTURBED SOIL SURFACE. WHEREVER EXCAVATION OCCURS BELOW THE DESIGNED FOUNDATION LEVEL, WELL COMPACTED BACK FILL OR LEAN CONCRETE SHALL BE USED FOR LEVELING.
- 4. BACKFILLING FOR FOUNDATION SHALL BE PLACED EVENLY IN 6" (150mm) LAYERS. LAYERS SHALL BE WELL COMPACTED.
- 5. THE FOUNDATION DESIGN IS SUITABLE FOR SOIL WITH A BEARING CAPACITY OF 1600 PSF (80 KPA) AND ABOVE.
- 6. THE FOUNDATION DESIGN IS SUITABLE FOR SOIL WITH FROST LINE OF 4' (1200 MM) OR LESS.





DOCUMENT No:		200-000-197						
REVISION HISTORY								
REV	DESCRIPTION		REF. No.	DATE	DRWN BY:	RWD BY:		
0	Initial Release for new	design	WO# 1912D	-	-			

ENGINEERING SEAL:

CLIENT:	STOCK	
PROJECT NAME:	STOCK	
DDODUOT NO.		

DX-1200

DRAWING TITLE:

MINI APOLLO FOUNDATION DRAWING

REV:	SHEET:		SHEET SIZE:	SCALE:
0	1 OF 1		PA3	NTS
DESIGNED BY: J. ZHAI		DATE: 2017-12-19		
DRAWN BY:	W. MCNAIR	DAT		018-09-20
CHECKED BY		DAT	E:	
REVIEWED B	Y:	DAT	E:	
APPROVED B	Y:	DAT	E:	



Email: info@dynamoplaygrounds.com

Fax: 613-446-0034 URL: www.dynamoplaygrounds.com