



GENERAL NOTES:

- 1. THE FOUNDATION IN THE DRAWING TO BE USED AS A MININUM GUIDELINE.
- 2. THE CONCRETE SHALL BE GRADE C25 (CHARACTERISTIC STRENGTH OF 3500 PSI AT 28 DAYS) MINIMUM.
- 3. THE FOUNDATION SHALL BE PLACED ON FIRM, UNDISTURBED SOIL SURFACE. WHEREVER EXCAVATION OCCURS BELOW THE DESIGNED FOUNDATION LEVEL, WELL COMPACTED BACK FILL OR LEAN CONCRETE SHALL BE USED FOR LEVELING.
- 4. BACKFILLING FOR FOUNDATION SHALL BE PLACED EVENLY IN 6" (150mm) LAYERS. LAYERS SHALL BE WELL COMPACTED.
- 5. THE FOUNDATION DESIGN IS SUITABLE FOR SOIL WITH A BEARING CAPACITY OF 1600 PSF (80 KPA) AND ABOVE.
- 6. THE FOUNDATION DESIGN IS SUITABLE FOR SOIL WITH FROST LINE OF 4' (1200 MM) OR LESS

4'-0" (1219 mm)

D	OCUMENT No:	200-000-201							
REVISION HISTORY									
REV	DESCRIPTION		REF. No.	DATE	DRWN BY:	RWD BY:			
0	Initial Release		1	-	-				

ENGINEERING SEAL:

CLIENT: STOCK
PROJECT NAME: STOCK

PRODUCT NO: DX-2300-F

DRAWING TITLE:

ASTRO W/FLOOR FOOTING DRAWING

REV:	SHEET:		SHEET SIZE:	SCALE:			
0	1 OF 1		PA3	NTS			
DESIGNED B'	_{Y:} JASON ZHAI	DAT		017-12-19			
DRAWN BY: WILL	IAM MCNAIR	DAT		018-04-17			
CHECKED BY	·:	DAT	E:				
CHECKED BY	JASON ZHAI	DAT		018-04-19			
REVIEWED B	Y:	DAT	E:				

PLAYGROUNDS Local: 613-446-0030

Toll free: 800-790-0034 Email: info@dynamoplaygrounds.com

Fax: 613-446-0034 URL: www.dynamoplaygrounds.com

1 PLAN VIEW - POST ONLY

4'-0" (1219 mm)