



GENERAL NOTES:

- 1. THE FOUNDATION IN THE DRAWING TO BE USED AS A MININUM GUIDELINE. CHECK WITH LOCAL ENGINEERS
- 2. THE CONCRETE SHALL BE GRADE C25 (CHARACTERISTIC STRENGTH OF 3500 PSI AT 28 DAYS) MINIMUM.
- 3. THE FOUNDATION SHALL BE PLACED ON FIRM, UNDISTURBED SOIL SURFACE. WHEREVER EXCAVATION OCCURS BELOW THE DESIGNED FOUNDATION LEVEL, WELL COMPACTED BACK FILL OR LEAN CONCRETE SHALL BE USED FOR LEVELING.
- 4. BACKFILLING FOR FOUNDATION SHALL BE PLACED EVENLY IN 6" (150mm) LAYERS. LAYERS SHALL BE WELL COMPACTED.
- 5. THE FOUNDATION DESIGN IS SUITABLE FOR SOIL WITH A BEARING CAPACITY OF 1600 PSF (80 KPA) AND ABOVE.
- 6. THE FOUNDATION DESIGN IS SUITABLE FOR SOIL WITH FROST LINE OF 4' (1200 MM) OR LESS.

DOCUMENT No:		200-001-069				
REVISION HISTORY						
REV	DESCRIPTION		REF. No.	DATE	DRWN BY:	RWD BY:
0	Initial Release		WO# 527	2020-05-07	WM	

ENGINEERING SEAL:

CLIENT:

STOCK STOCK

PROJECT NAME: PRODUCT NO:

DX-814

DRAWING TITLE:

BEEHIVE WITH PLANAR NETS FOUNDATION DRAWING

REV: SHEET: SHEET SIZE: SCALE:

O 1 OF 2 PA3 NTS

DESIGNED BY: DATE:

DRAWN BY: W. MCNAIR 2020-05-07

CHECKED BY: DATE:

REVIEWED BY: DATE:

APPROVED BY: DATE:



Local: 613-446-0030 Toll free: 800-790-0034

Email: info@dynamoplaygrounds.com

Fax: 613-446-0034 URL: www.dynamoplaygrounds.com

