


PRODUCT SPECIFICATION



 Product Name
 The Spider

 Product Number
 IM-1015

 Size -- Length
 4.19 m / 13' 9"

 Size -- Width
 2.63 m / 8' 8"

 Size -- Height
 I.86 m / 6' I"

Foundations 9

Concrete Volume 1.20 m³ / 42.4 ft³

	ASTM F-1487	CSA Z614	EN 1176
Ages	5 years - 12 years	5 years - 12 years	6 years - 12 years
Capacity	8	8	8
Use Zone Length	7.85 m / 25' 9"	7.85 m / 25' 9"	7.19 m / 23' 7"
Use Zone Width	6.29 m / 20' 8"	6.29 m / 20' 8"	5.63 m / 18' 6"
Fall Height	I.86 m / 6' I"	1.86 m / 6' 1"	1.86 m / 6' 1"

*Note: Concrete must be minimum 3500 PSI / 25MPa

Product Features:

CONTOURED POSTS: This will be 3 1/2" (90mm) OD schedule 40 phosphate dipped steel tubing,

finished with polyester powder coating.

20MM ROPE: These will be 20 mm diameter polyamide (nylon) rope cable with UV protection

and fire retardant solution that is manufactured in house by Dynamo. Each rope consists of 6 strands each containing 24 galvanized steel reinforcing wires within a polyamide (nylon) braid, wrapped around a solid polyamide (nylon) core for a total of 144 galvanized steel reinforcing strands. Rope shall achieve a Class 7-8

Colourfastness rating.

BALL KNOTS: This will be a one-piece compressed aluminum ball, compressed in place with

150,000 pounds force (667 kN) to prevent the connection from moving and

causing premature cable wear.

IGLOO CONNECTOR: This will be a stainless steel connector allowing for 1 plane of motion. The male

end of the connector is secured to the rope ends with a stainless steel sleeve

which is bolted to the female end on the frame.

BASIC FASTENERS: All fasteners for component attachments are stainless steel.

MOUNTING PLATES: These will be made of galvanized steel. Mounting plates will be secured to

concrete blocks with expansion bolts.

SURFACE MOUNT: This product will be surface mounted utilizing 6" (150mm) long expansion bolts.

INSTALLATION: This should be installed only by a licensed playground installer, trained and

certified on the relevant playground standards in place in the region of installation,

e.g., NPSI, CPSI or similar certified.

COMPLIANT WITH: CAN/CSA-Z614-07

ASTM F-1487-11

EN-1176

CPSC Handbook for Public Playground Safety





PRODUCT SPECIFICATION









o Connector Expansion B

P: 1-800-790-0034 / 613-446-0030 F: 613-446-0034 W: www.dynamoplaygrounds.com

