

Product Name	Mid-Size Apollo™
Product Number	DX-2000
Size -- Diameter	3.30 m / 10' 10"
Size -- Height	3.32 m / 10' 11"
Shipping Weight	515 kg / 1135.4 lb
Shipping Volume	3.10 m ³ / 109.5 ft ³
Foundations	1
Concrete Volume	No Concrete Required


	ASTM F-1487	CSA Z614	EN 1176
Ages	5 years - 12 years	5 years - 12 years	5 years - 12 years
Capacity	25	25	25
Use Zone -- Diameter	7.30 m / 23' 11"	8.70 m / 28' 7"	7.30 m / 23' 11"
Fall Height	2.00 m / 6' 7"	2.04 m / 6' 8"	2.04 m / 6' 8"




Product Features:

- MAIN SUPPORT POST:** This inner support post provides support and stability to the rotational system. This will be constructed of 5 1/2" (139.8mm) OD schedule 40 galvanized steel pipe, mounted to a reinforced steel base with braces.
- ROTATIONAL POST:** This outer support post provides the anchoring point for climbing nets and allows the unit to rotate as one. This will be constructed from 6 5/8" (168mm) OD schedule 10 galvanized steel pipe finished with polyester powder coating. The top will be finished with a 1/4" (9mm) thick top plate. Integrated climbing net connection points will be included on the top plate and along the rotational support post as required. Integrated connection points for the deck will also be provided as required.
- ROTATION:** The Rotational Post will rotate along with all other parts of the play equipment in a way that prevents clothing entanglements or pinching.
- HORIZONTAL RINGS:** These will be 3" (75mm) OD galvanized steel tubing finished with polyester powder coating. Rings will include integrated climbing net connections points as required.
- 20MM ROPE:** These will be 20 mm diameter polyamide (nylon) rope cable with UV protection and fire retardant solution that is manufactured in house by Dynamo. Each rope consists of 6 strands each containing 24 galvanized steel reinforcing wires within a polyamide (nylon) braid, wrapped around a solid polyamide (nylon) core for a total of 144 galvanized steel reinforcing strands. Rope shall achieve a Class 7-8 Colourfastness rating.
- NET CONNECTIONS:** Each location where the climbing nets meet the ring or post will have a one-piece stainless steel junction sleeve compressed onto the rope and affixed to the post or ring connector with a bolt and nut.


BALL KNOTS:	This will be a one-piece compressed aluminum ball, compressed in place with 150,000 pounds force (667 kN) to prevent the connection from moving and causing premature cable wear.
BASIC FASTENERS:	All fasteners for component attachments are stainless steel.
BEARINGS:	This will be maintenance-free self-lubricating nylon, sealed and integrated into the central post, leaving no apparent mechanism.
FOOT BASE:	This will be 4' x 4' (1220mm x 1220mm) galvanized steel plates, 3/16" (5mm) thick, attached to the support posts with 2" x 2" (50mm x 50mm) galvanized angle steel braces and buried under 4' 6" (1370mm) of fill mass for stability.
INSTALLATION:	This should be installed only by a licensed playground installer, trained and certified on the relevant playground standards in place in the region of installation, e.g., NPSI, CPSI or similar certified.
NO-ENCROACHMENT ZONE:	Where required, this will be an obstacle-free zone that does not necessarily meet the requirements of the protective surfacing zone. See applicable standard for more information.
COMPLIANT WITH:	CAN/CSA-Z614-07 ASTM F-1487-11 EN-1176 CPSC Handbook for Public Playground Safety
TÜV CERTIFIED:	Certified to EN 1176:2008 TÜV Rhineland Certificate N° AK50084826
IPEMA CERTIFIED:	The DX-2000 identified in this specification sheet is IPEMA certified. The use and layout of the DX-2000 conforms to the requirements of ASTM F1487 and CSA Z614. To verify product certification visit www.ipema.org .



Support Posts



Climbing Net - 20 mm




Net Connector



Ball Knot



Top Bearing



Bottom Bearing