



Product Name	Cedar Bench 6'
Product Number	NP-CCB183
Size -- Length	1.83 m / 6' 0"
Size -- Length	0.61 m / 2' 0"
Size -- Width	0.51 m / 1' 8"
Shipping Weight	308 kg / 679.0 lb
Shipping Volume	0.60 m <sup>3</sup> / 21.2 ft <sup>3</sup>
Foundations	1

	<b>ASTM F-1487</b>	<b>CSA Z614</b>	<b>EN 1176</b>
Ages	2 years - 12 years	2 years - 12 years	3 years - 12 years
Capacity	3	3	3
Use Zone -- Length	5.49 m / 18' 0"	5.49 m / 18' 0"	4.83 m / 15' 10"
Use Zone -- Width	4.27 m / 14' 0"	4.27 m / 14' 0"	3.61 m / 11' 10"
Fall Height	0.51 m / 1' 8"	0.51 m / 1' 8"	0.51 m / 1' 8"

## Product Features:

<b>CONSTRUCTION:</b>	Manufactured from colour-integrated Glass Fiber Reinforced Concrete (GFRC) over structural steel frame. Glass Fiber is Alkali-Resistant type glass formulated for concrete. GFRC shall be 1500 PSI (10.3 MPa) in tension, 5000 PSI (34.5 MPa) in compression.
<b>GFRC COLOURING:</b>	Hardened GFRC is coloured with Alkali reactive chemical stain, which permanently changes the surface colour of the concrete. Final colouring is achieved with latex stain made for concrete.
<b>GFRC REPAIR:</b>	GFRC is readily repairable no matter the age of the material.
<b>COMPLIANT WITH:</b>	<b>CAN/CSA-Z614-07</b> <b>ASTM F-1487-11</b> <b>EN-1176</b> <b>CPSC Handbook for Public Playground Safety</b>
<b>INSTALLATION:</b>	This should be installed only by a licensed playground installer, trained and certified on the relevant playground standards in place in the region of installation, e.g., NPSI, CPSI or similar certified.
<b>NATUREPLAY WARRANTY:</b>	Dynamo Industries (Manufacturer) warrants all Dynamo ROCKS! products (Products) to be free from defect in materials or workmanship for a period of (1) one year during normal use and installation and in accordance with our published specifications. If the purchaser discovers within this period a failure of the product to conform to specifications, or a defect in material or workmanship, the purchaser must promptly notify Manufacturer in writing within fifteen (15) days of discovering the defect. Within a reasonable time after notification, at the sole option of Manufacturer, Manufacturer shall perform a repair or correct these products if defective in manufacturing workmanship, materials or parts only, labour is excluded. Dynamo additionally offers a Ten-year limited warranty against structural failure due to natural deterioration or manufacturing defects.

This warranty does not apply to:

1. Damage resulting from improper use.
2. Any product, component or part not supplied by Manufacturer.
3. Defects generated by uses other than those for which it was created.
4. Damage resulting from vandalism.
5. Damage resulting from natural catastrophic events.
6. Normal expected wear or weathering such as colour changes, minor scratches, minor chipping or normal weather-related stains.
7. Efflorescence as a natural curing by-product of GFRC.
8. Accidents, injuries or liabilities which result from the use of Products or services.
9. Damage caused during shipment.
10. Damage which results from incorrect installation that does not conform to published instructions and specifications.

These warranties cover either replacement or repair, at the Manufacturer's discretion, of any Products according to the above descriptions. Transportation and installation-on-site costs are not covered by these warranties, except where specific arrangements are made with written consent from the Manufacturer.

This warranty period of 1 year begins on the date that Products are shipped. The warranty starting and ending dates do not coincide with payment dates or the completion of work done by others. Warranty is void if sand or pea gravel safety surfacing is used as a resilient surface under products. NOTE: All concrete has naturally occurring hairline cracks and these are not product defects.

To make claim under the terms of the Warranty, the Buyer's written statement of claim, along with a copy of the original invoice, maintenance records, and supporting photographs, must be sent to the below listed address.

