



Product Name	Staggered Stumps
Product Number	NP-AP020
Approx. Size -- Length	2.08 m / 6' 10"
Approx. Size -- Width	0.96 m / 3' 2"
Approx. Size -- Height	0.94 m / 3' 1"
Shipping Weight	590 kg / 1300 lb
Foundations	1
Concrete Volume	0.35 m ³ / 12.4 ft ³

	ASTM F-1487	CSA Z614	EN 1176
Ages	2 years - 12 years	18 months - 12 years	2 years - 12 years
Use Zone -- Length	5.74 m / 18' 10"	5.68 m / 18' 8"	5.08 m / 16' 8"
Use Zone -- Width	4.62 m / 15' 2"	4.56 m / 15' 0"	3.96 m / 13' 0"
Use Zone -- Area	20.98 m ² / 225.8 ft ²	20.45 m ² / 220.1 ft ²	15.85 m ² / 170.6 ft ²
Fall Height	0.94 m / 3' 1"	0.94 m / 3' 1"	0.94 m / 3' 1"

*Note: Concrete must be minimum 4000 PSI / 30MPa



Product Features:

CONSTRUCTION:	Manufactured from colour-integrated Glass Fiber Reinforced Concrete (GFRC) over structural steel frame. Glass Fiber is Alkali-Resistant type glass formulated for concrete. GFRC shall be 1500 PSI (10.3 MPa) in tension, 5000 PSI (34.5 MPa) in compression.
GFRC COLOURING:	Hardened GFRC is coloured with Alkali reactive chemical stain, which permanently changes the surface colour of the concrete. Final colouring is achieved with latex stain made for concrete.
GFRC REPAIR:	GFRC is readily repairable no matter the age of the material.
COMPLIANT WITH:	CAN/CSA-Z614 ASTM F-1487 EN-1176 CPSC Handbook for Public Playground Safety
INSTALLATION:	This should be installed only by a licensed playground installer, trained and certified on the relevant playground standards in place in the region of installation, e.g., NPSI, CPSI or similar certified.

